

ISO/IEC JTC1/SC17 N 3919

DOCUMENT TYPE: TEXT FOR FDIS BALLOT

TITLE: Notification that – ISO/IEC FDIS 15693-1 Identification cards – Contactless integrated circuit cards – Vicinity cards – Part 1: Physical characteristics – has been posted to the ISO server for FDIS ballot

BACKWARD POINTER: N 3619, N 3644, N 3693, N 3805 and N 3918.

SOURCE: SECRETARIAT ISO/IEC JTC1/SC17

STATUS: Notification of FDIS ballot

ACTION ID: LB


WORK ITEM: 39694

DUE DATE: To be advised by ISO

DISTRIBUTION P, L and O-Members of ISO/IEC JTC1/SC17
JTC1 Secretariat
ISO/IEC ITTF

MEDIUM: SERVER

NO. OF PAGES: 9

	Explanatory Report	ISO/IEC FDIS
	ISO/IEC JTC 1/SC17 N 3919 Will supersede: SC 17 N 3805	Secretariat: APACS for BSI

This form should be sent to ITTF, together with the committee draft, by the secretariat of the joint technical committee or sub-committee concerned

The accompanying document is submitted for circulation to member body vote as a FDIS, following consensus of the P-members of the committee obtained on:	
	at the {DATE, LOCATION} meeting of ISO/IEC JTC 1/SC {YY} (See resolution number {XX} in document SC {YY} N {XXXXXX})
✓	by postal ballot initiated on: 2009-06-26
P-members in favour:	Austria (ASI), Canada (SCC), China (SAC), Czech Republic (UNMZ), Denmark (DS), France (AFNOR), Germany (DIN), India (BIS), Italy (UNI), Japan (JISC), Korea, Republic of (KATS), Netherlands (NEN), Norway (SN), Poland (PKN), Singapore (SPRING SG), Switzerland (SNV), United Kingdom (BSI), USA (ANSI)
P-members voting against:	
P-members abstaining:	Australia (SA), Belgium (NBN), Finland (SFS), Israel (SII), Malaysia (DSM), Portugal (IPQ), Slovakia (SUTN), South Africa (SABS), Spain (AENOR), Sweden (SIS)
P-members who did not vote:	Armenia (SARM), Kenya (KEBS), Romania (ASRO), Russian Federation (GOST R)

Remarks:

Disposition of comments for the FCD is contained in 17n3918.

Project: 39694

I hereby confirm that this draft meets the requirements of part 2 of the IEC/ISO Directives

Date:
2010-04-30

Name/Signature of the secretary:

Chris Starr

ISO/IEC JTC1/SC17/WG8 N

Date: 2009-12-04

ISO/IEC FDIS 15693-1:2010

Secretariat:

**Identification cards – Contactless integrated circuit cards – Vicinity cards –
Part 1: Physical characteristics**

Contents

1	Scope.....	1
2	Normative references	1
3	Terms and definitions.....	1
4	Physical characteristics	2
4.1	General.....	2
4.2	Antenna.....	2
4.3	Alternating magnetic field.....	2
4.4	Additional information.....	2
	Annex A (informative) Surface quality for printing	Error! Bookmark not defined.
	Annex B (informative) Hole slot	3
	Bibliography	4

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO/IEC JTC1 shall not be held responsible for identifying any or all such patent rights.

International Standard ISO/IEC 15693-1 was prepared by Joint Technical Committee ISO/IEC JTC1, *Information technology*, Subcommittee SC17, *Cards and personal identification*.

This second edition cancels and replaces the first edition (ISO/IEC 15693-1:2000).

ISO/IEC 15693 consists of the following parts, under the general title *Identification cards - Contactless integrated circuit cards - Vicinity cards*:

- *Part 1: Physical characteristics*
- *Part 2: Air interface and initialization*
- *Part 3: Anticollision and transmission protocols*

Annexes A and B of this part of ISO/IEC 15693 are for information only.

Introduction

Contactless card standards encompass a variety of types as embodied in International Standards ISO/IEC 10536 (Close-coupled cards), ISO/IEC 14443 (Proximity cards) and ISO/IEC 15693 (Vicinity cards). These device types are intended, respectively, for operation when very near, nearby and at a longer distance from associated coupling devices.

ISO/IEC 15693 defines the technology-specific requirements for identification cards conforming to ISO/IEC 7810 and thin flexible cards conforming to ISO/IEC 15457-1 and the use of such cards to facilitate international interchange. However, it also recognizes that the technology offers the possibility that vicinity objects may be provided in forms other than that of the international standard card formats. Furthermore, it does not preclude the incorporation of other standard technologies on the card, such as those referenced in the bibliography.

ISO/IEC 15693 accommodates the operation of Vicinity cards in the presence of other contactless cards conforming to ISO/IEC 10536 and ISO/IEC 14443 standards.

Identification cards – Contactless integrated circuit cards – Vicinity cards – Part 1: Physical characteristics

1 Scope

This part of ISO/IEC 15693 describes the physical characteristics of vicinity cards (VICCs).

It is used in conjunction with other parts of ISO/IEC 15693.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 7810, *Identification cards – Physical characteristics*

ISO/IEC 15457-1, *Identification cards – Thin flexible cards – Physical characteristics*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/IEC 7810, ISO/IEC 15457-1 and the following apply.

3.1 integrated circuit IC

electronic component designed to perform processing and/or memory functions

3.2 contactless

pertaining to the achievement of signal exchange with, and supply of power to, the card without the use of galvanic elements (i.e. the absence of an ohmic path from the external interfacing equipment to the integrated circuit contained within the card)

3.3 contactless integrated circuit card

card into which integrated circuit and coupling means have been placed, such that communication to such integrated circuit is done in a contactless manner

3.4 operate as intended

operates in the manner described by the manufacturer's specification in accordance with the ISO/IEC 15693 series

3.5 VICC

contactless integrated circuit card or other object with which communication and power transfer are done by inductive coupling in vicinity of a coupling device; commonly called a vicinity card

4 Physical characteristics

4.1 General

The VICC may be in the form of a card compliant with ISO/IEC 7810 or ISO/IEC 15457-1, or an object of any other dimension.

4.2 Antenna

If the VICC dimensions are not compliant with ISO/IEC 7810 or ISO/IEC 15457-1, to maximize interoperability, the dimensions of the VICC antenna shall not exceed 86 mm x 54 mm x 3 mm.

NOTE This antenna size restriction stems from the fact that the radio frequency power and signal interface defined in ISO/IEC 15693-2 and its test methods in ISO/IEC 10373-7 are based on ID-1 cards. The test methods may give unreliable results with antennas larger than that defined above.

4.3 Alternating magnetic field

The VICC, whichever form the VICC has according to 4.1, shall continue to operate as intended after continuous exposure to a magnetic field of an average level of 10 A/m rms at 13,56 MHz. The averaging time is 30 seconds and the maximum level of the magnetic field is limited to 12 A/m rms.

4.4 Additional information

Surface quality for printing should be as shown in Annex A.

When a hole slot is optionally implemented, the slot should be as shown in Annex B.

Annex A
(informative)
Surface quality for printing

Where there is a requirement to customize the VICC after the manufacturing process by overprinting, care should be taken to ensure the areas used for printing are of sufficient quality appropriate to the printing technique or printer used.

Annex B (informative) Hole slot

When a slot is optionally implemented the slot size and slot location should be as shown in either Figure B.1 or Figure B.2.




Figure B.1 — Hole Slot for Portrait Orientation




Figure B.2 — Hole Slot for Landscape Orientation

The VICC IC(s) and inductive coupling element shall be positioned such that either slot as shown in Figure B.1 and Figure B.2 can be implemented without interference to either the IC(s) or inductive coupling element.

WARNING — Cards with hole slots may cause problems in automatic card handling equipment, for example cash dispensers.

Bibliography

This part of ISO/IEC 15693 does not preclude the application to the VICC of other existing card technology standards, such as those listed as follows:

- ISO/IEC 7811(all parts), *Identification cards - Recording technique*;
- ISO/IEC 7812(all parts), *Identification cards - Identification of issuers*;
- ISO/IEC 7813, *Identification cards - Financial transaction cards*;
- ISO/IEC 7816(all parts), *Identification cards - Integrated circuit cards*;
- ISO/IEC 10536(all parts), *Identification cards - Contactless integrated circuit(s) cards - Close-coupled cards*;
- ISO/IEC 10373-7, *Identification cards – Test methods - Vicinity cards*;
- ISO/IEC 14443(all parts), *Identification cards - Contactless integrated circuit cards - Proximity cards*;
- ISO/IEC 15457(all parts), *Identification cards – Thin flexible cards*;

NOTE Restrictions may apply to embossing of VICCs (see ISO/IEC 7811-□).